

RESET

PURPOSE

Resets all internal DATAPLOT parameters, variables, functions, and switches to default sign-on conditions.

DESCRIPTION

The RESET command allows the analyst to clear all of DATAPLOT's internal settings so as to start afresh.

SYNTAX 1

RESET

This syntax resets all internal settings.

SYNTAX 2

RESET <keyword>

where <keyword> is one of the following:

ALL	- reset all internal settings
CONTROL	- reset the plot control settings
DATA	- reset the data settings
SUPPORT	- resets the support settings
GRAPHICS	- resets the graphics settings
I/O	- resets the I/O settings
CLSB	- resets the CHARACTER, LINE, SPIKE, and BAR switches
LIMITS	- resets the LIMITS settings
VARIABLES	- reset variable settings
PARAMETERS	- reset parameter settings
FUNCTIONS	- reset function settings
MATRICES	- reset matrix settings.

EXAMPLES

RESET

RESET DATA

RESET LIMITS

DEFAULT

None

SYNONYMS

CLEAR

RELATED COMMANDS

SAVE MEMORY	=	Dumps all of DATAPLOT's internal parameters, variables, functions, and switches to a file.
DIMENSION	=	Set the number of columns and rows for DATAPLOT's work array.

APPLICATIONS

Interactive convenience

IMPLEMENTATION DATE

Pre-1987 (SYNTAX 2 was implemented 92/1 and updated 93/9)